


CE
RoHS

08H2038-050-4BL
DINGS' MOTION
DATE


REVISION			
REV.	DATE	DESCRIPTION	DRAWN BY



Motor's phase	2
Step angle($\pm 5\%$)	1.8°
Rated current/phase	0.5A
Resistance/phase(20°C)	8.8 Ω $\pm 10\%$
Inductance/phase(1V,1kHz)	2.7mH $\pm 20\%$
Holding torque/2 phase	0.02N.m
Rotary inertia	3.3g.cm ²
Insulation class	B
Insulation resistance	100M Ω (500VDC)
Heat rise	80°C
Motor weight	0.08kg

NOTICE TO PERSONS RECEIVING THIS DRAWING
THIS DRAWING IS ONLY CONDITIONALLY ISSUED, AND FOR THE SOLE PURPOSE OF INFORMING LICENSEES AND ASSOCIATE CONTRACTORS OF DINGS' MOTION, AND VENDORS THERETO AND CUSTOMERS THEREOF, RECEIPT OR POSSESSION THEREOF DOES NOT CONFER TO TRANSFER ANY RIGHT IN THE SUBJECT MATTER OF THE DRAWING. THE DESIGN, CONSTRUCTION, TECHNICAL INFORMATION AND ALL OTHER SUBJECT MATTER SHOWN IN THIS DRAWING ARE AND REMAIN, EXCEPT AS MAY BE OTHERWISE INDICATED BY WRITTEN NOTICE HEREON, THE EXCLUSIVE PROPERTY OF SAID CORPORATION. THIS DRAWING MAY BE REPRODUCED ONLY BY LICENSEES AND ASSOCIATE CONTRACTORS OF SAID CORPORATION AND ONLY FOR LICENSED MANUFACTURE, AND BY VENDORS MANUFACTURING FOR SAID CORPORATION AND ONLY FOR LICENSEES AND ASSOCIATE CONTRACTORS.

CUSTOMER



EXCITING SEQUENCE

CW	→			
Red A+	+		-	
Red/wht A-	-		+	
Green B+		+		-
Grn/wht B-		-		+
CCW	←			

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MILLIMETERS AND TOLERANCES ARE AS BELOW PER ISO2768-ck.

LINEAR		ANGLUR	
0~3	± 0.2	0~10	$\pm 1.5^\circ$
3~6	± 0.5	10~50	$\pm 1^\circ$
6~30	± 0.8	50~120	$\pm 30'$
30~120	± 1.5	120~400	$\pm 15'$

DRAWN	Long	DATE	2022/6/14
APPRVD		DATE	
MODEL	08H2038-050-4BL		

DINGS

SIZE	A3	SHEET	1 OF 1
SCALE	1: 1	REV	00